

AMSEC

COMMERCIAL SAFES



Table of Contents

RMM Series 4

MM Series 5

BWB Drop Series 6

BWB Series7

DSF Series..... 8

DSR Series..... 9

BLC Series..... 10

BLB Series11

CFX Series.....12

CF Series 13

CE Series 14

DXE Series.....16

ACF Series.....18

TB Series 20

AMSEC Electronic Locks21

Partner Electronic Locks..... 22

Partner Mechanical Locks 23

About Us

At AMSEC, we have been dedicated to providing quality security solutions to our customers since our establishment in 1946.

Additionally, AMSEC entered the Smart Safe market 10 years ago with CashWizard, securing two more patents for our Smart Safe technology. The CashWizard Smart Safe is the highest security depository safe of its kind on the market today and provides ultimate visibility into daily cash transactions via integrated cloud-based software that gives treasury and other management suites the ability to remotely manage money from anywhere in the world, 24 hours a day, 7 days a week.

At AMSEC, we believe that innovation is not just about creating new products but also improving existing ones. We continuously update our products to keep up with the latest technology and security standards, ensuring that our customers have the best possible experience with our products.

Our humble beginnings started with little more than a welder, lathe, and a desire to build strong safes. As we’ve grown, we’ve expanded our offerings to meet the changing needs of our customers. Through dedication and hard work, we have become a leading name in the security industry, providing a wide range of products and services, including our CashWizard Smart Safes.

Over the years, we’ve had the privilege to work with a diverse range of clients across various industries and have been recognized for our commitment to quality and excellence. At AMSEC, our core values guide us in everything we do. We are committed to providing the highest level of security solutions to our customers and continuously strive to innovate and improve our offerings.

Product Information Disclaimer

The information and specifications provided in this catalog are believed to be accurate at the time of printing. AMSEC reserves the right to modify product designs, specifications, and materials without notice.

RMM Series



Product Overview

AMSEC’s RMM Series (Retail Money Manager) safes are purpose-built for modern cash management, combining robust security with smart design features. As the industry’s #1 selling cash management safe line, the RMM Series has earned its reputation by helping businesses like convenience stores, restaurants, and retail shops secure their daily revenue with confidence. Constructed with a formidable 1/2-inch-thick solid steel plate door and a reinforced high-tensile steel body, these safes resist prying, sledgehammer attacks, and drilling attempts. Each safe is equipped with multiple anti-theft measures such as 10 anti-spread door pins and auxiliary relocking devices for maximum protection.

Beyond brute strength, the RMM Series offers practical cash-handling conveniences. A large deposit drawer allows staff to drop cash deposits quickly into an internal locker without opening the main safe, reducing exposure and keeping cash secured at all times. Removable coin racks on the door provide organized storage for change, and an inner compartment can store cash tills or high-value items separately. Advanced electronic locks (including audit-trail capable options like the ESLAudit II) ensure that access is controlled and documented, enhancing accountability. With its space-efficient under-counter design and proven reliability, the RMM Series delivers total cash control and peace of mind for busy operations.



Textured
Charcoal Gray

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
RMM2620SW-R	26" x 20" x 18 ½"	18 ¼" x 15 ½"	11 GA	4.6 cu. ft.	230 lbs.	SafeWizard II
RMM2620ESLAudit-R	26" x 20" x 18 ½"	18 ¼" x 15 ½"	11 GA	4.6 cu. ft.	230 lbs.	ESLAudit II
RMM2620ESL20-R	26" x 20" x 18 ½"	18 ¼" x 15 ½"	11 GA	4.6 cu. ft.	230 lbs.	ESL20
RMM3124ESLAudit	31" x 24 ½" x 20"	Left: 28" x 13 ½" Right: 12 ⅝" x 5 ¾"	11 GA	Left: 4.76 cu. ft. Right: 2.16 cu. ft.	360 lbs.	ESLAudit II

Left-swing door available on RMM2620 models only.

- **1/2-inch-thick solid steel plate door with 10 anti-spread pins:** Resists prying attacks.
 - **Three-way locking with five large bolts:** Multi-point locking maximizes security.
 - **Quick “drop” deposit drawer:** Allows deposits without opening the safe.
 - **Internal locking compartment:** Separates and secures dropped deposits from main storage.
 - **Door-mounted coin racks:** Organize coins and change for daily operations.
- **Reinforced steel body construction:** High-tensile steel walls resist attack.
 - **Advanced electronic locks with audit trail:** Audit-trail locks track access.
 - **Compact under-counter design:** Fits below counters for discreet, space-saving use.
 - **Anchorable heavy-duty safe:** Pre-drilled anchor holes allow bolting the safe to floors or counters for stability.
 - **Ideal for retail and C-store use:** Ideal for high-cash, multi-employee businesses.

MM Series



Product Overview

AMSEC’s Money Manager (MM) Series safes are B-rated, under-counter depository safes engineered to give businesses total cash control over their daily receipts. Each MM Series safe features a dual-door design: a top compartment that serves as a receiving locker for quick cash deposits, and a lower compartment that provides secure storage for cash trays, coin rolls, or other valuables. This innovative layout allows managers to segregate and secure drops during a shift while still having easy access to change and till drawers for daily operations. The MM Series supports multiple deposit configurations – including models with front-loading or top-loading slots and even tri-slot setups with color-coded drop chutes for sorting cash by denomination or shift.

Built to the same robust standards as AMSEC’s other cash safes, the Money Manager Series boasts a solid steel plate door and heavy gauge steel body to resist attacks. Three substantial locking bolts, internal relocking devices, and a hardened steel plate shield the lock mechanism from drilling or punching attempts. Anti-fish baffles on the deposit slots prevent thieves from retrieving contents through the drop slot. With a roomy interior capable of holding up to four standard cash tills, the MM Series streamlines cash handling for businesses, all while keeping your funds protected and organized.



Textured
Charcoal Gray

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
MM2820 CTR-Drop-E2	28" x 20 ½" x 20"	TOP: 8 ½" x 16 ¼" BTM: 8 ½" x 16 ¼"	11 GA	1.87 cu. ft. 2.16 cu. ft.	278 lbs.	ESL20
MM2820 CTRDrop-ESLAudit	28" x 20 ½" x 20"	TOP: 8 ½" x 16 ¼" BTM: 8 ½" x 16 ¼"	11 GA	1.87 cu. ft. 2.16 cu. ft.	278 lbs.	ESLAudit II

- **Dual-door safe for deposits & storage:** Separate top deposit locker and lower cash storage compartment.
 - **Multiple drop slots (top/front):** Models available with various deposit slot configurations, including triple-drop options.
 - **Color-coded drop bins:** Sort deposits by shift or type for easier cash management.
 - **Holds up to four cash till trays:** Spacious lower compartment fits standard cash drawers for end-of-day storage.
 - **Solid steel B-rated construction:** Thick steel plate door and body provide rugged burglary protection.
- **Three 1-inch diameter locking bolts:** Three large steel bolts secure the door on multiple sides to prevent prying.
 - **Internal relocker & hardplate:** Relocking device and hardened steel plate shield the lock against attack.
 - **Anti-fish deposit baffles:** Special baffle design stops thieves from fishing out deposits through the slot.
 - **Anchorable heavy-duty safe:** Pre-drilled anchor holes allow bolting the safe to floors or counters for stability.
 - **Boosts cash-handling efficiency:** Improves shift accountability and reduces losses by securing cash drops immediately.

BWB Drop Series



Product Overview

The BWB Drop Series safes are wide-body depository safes designed for businesses that demand quick deposit capability and ample internal space for cash storage. These safes are built with B-rated heavy-duty construction, including up to a 1/2-inch-thick solid steel plate door and thick steel walls, to resist forced entry attempts. Each safe features a front or top-loading deposit slot (depending on model) equipped with saw-toothed anti-fish baffles to prevent retrieval of dropped items. This allows employees to securely drop cash, checks, or envelopes into the safe throughout the day without needing to open the main door.

Inside the BWB Drop Series, the wide interior compartment is spacious enough to accommodate entire cash register tills or bulk valuables, making end-of-day lockup quick and easy. Additional features like a hardened steel locking mechanism with five large live bolts, spring-loaded relocking devices, and a drill-resistant hardplate protect against attacks. For convenience, a recessed coin rack is often built into the door to organize change. The BWB Drop Series comes in various sizes and configurations, all designed to keep high-volume cash operations secure and efficient.



Textured
Charcoal Gray

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
BWB2020FL	29 ¾" x 20" x 20"	14 ¾" x 16 ¼"	11 GA	1.74 cu. ft.	218 lbs.	ESL10
BWB3020-D1	30" x 20" x 20"	24 ¾" x 16 ¼"	11 GA	3.7 cu. ft.	270 lbs.	Mechanical
BWB3020FL	39 ¾" x 20" x 20"	24 ¾" x 16 ¼"	11 GA	3.7 cu. ft.	278 lbs.	ESL10
BWB4020FL	49 ¾" x 20" x 20"	34 ¾" x 16 ¼"	11 GA	5.63 cu. ft.	360 lbs.	ESL10

- **11-gauge body & 1/2-inch-thick steel door:** Tough B-rated construction resists prying and drilling.
 - **Front or top deposit slot:** Drop cash without unlocking the safe.
 - **Anti-fish baffle design:** Saw-tooth baffles prevent fishing out deposits.
 - **Five 1-inch diameter locking bolts:** 3-way boltwork with five 1-inch diameter bolts secures the door.
 - **Spring-loaded relocker:** Re-locks bolts if lock is tampered.
- **Spacious wide interior:** Fits full cash trays and bulk valuables.
 - **Interior locker:** An Inner compartment keeps deposits separate.
 - **Door-mounted coin rack:** Built-in holder for rolled coins.
 - **Bolt-down ready for stability:** Pre-drilled anchor holes for floor mounting.
 - **Ideal for cash-heavy businesses:** Great for retail stores, restaurants, and gas stations.

BWB Series



Product Overview

The BWB Series wide-body safes are tough, B-rated business safes built to securely hold cash register drawers and other valuables. They're ideal for quick access to change, deposits, and daily cash storage needs. Built with security at its core, each BWB safe features a recessed 1/2-inch-thick solid steel plate door engineered to resist pry attacks, and a reinforced steel body with continuous welds for strength. A three-way locking mechanism with five 1-inch diameter chromed steel bolts secures the door on all sides when locked, and internal jamb reinforcements on all four sides add extra protection against sledgehammer strikes.

Inside, the wide design offers practical storage for businesses: you can fit entire till trays without having to remove the cash, making end-of-day safe storage fast and easy. Adjustable shelves help organize the interior for money bags, receipts, or other items, and a recessed coin rack on the door provides a handy spot for rolled coins or change. Additional security enhancements include a large carburized hardplate that shields the lock and relocker from drills, and a spring-loaded relocking device that triggers if the lock is attacked. Four anchor bolt holes in the bottom allow you to bolt the safe securely to the floor for added security. With its compact under-counter profile and heavy-duty design, the BWB Series is a go-to choice for small businesses that need reliable cash protection every day.



Textured
Charcoal Gray

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
BWB2020	20" x 20" x 20"	14 ¾" x 16 ¼"	11 GA	3.83 cu. ft.	154 lbs.	ESL10
BWB3020	30" x 20" x 20"	24 ¾" x 16 ¼"	11 GA	5.78 cu. ft.	218 lbs.	ESL10
BWB4020	40" x 20" x 20"	34 ¾" x 16 ¼"	11 GA	7.72 cu. ft.	272 lbs.	Mechanical Lock

- **1/2-inch-thick solid steel plate door:** Thick, pry-resistant door provides B-rated burglary protection.
 - **Five 1-inch diameter locking bolts:** Three-way boltwork with five chromed steel bolts secures the door on all sides.
 - **Reinforced door jamb & dead bar:** Strengthened frame and hinge-side dead bar thwart prying or door removal.
 - **Large wide-body interior:** Spacious design fits full cash register trays and bulky valuables with ease.
 - **Adjustable shelving:** Removable shelves for organizing contents.
- **Door-mounted coin rack:** A built-in coin rack keeps spare change organized.
 - **Drill-resistant hardplate:** Hardened plate protects lock from drilling attacks.
 - **Spring-loaded relocker:** Internal relocker triggers if lock is punched, keeping bolts locked.
 - **UL-listed lock:** High-security combination or digital locks meet UL security standards.
 - **Easy under-counter installation:** Pre-drilled anchor holes for bolting down, ideal for under-counter use.

DSF Series



Product Overview

AMSEC's DSF Series safes are front-loading depository safes designed to provide immediate, secure storage for cash deposits in businesses. Each DSF safe features a deposit hopper on the front of the safe. Employees can drop cash, checks, or envelopes through this hopper, where they fall into a secure compartment inside the safe. This setup means staff can deposit funds quickly throughout the day without needing to open the safe, reducing exposure of cash. To retrieve deposits, an internal receiving compartment (accessible via a separate locked door) keeps those funds secure from unauthorized access until a manager can collect them.

Built with rugged B-rate construction, DSF Series safes utilize a 1/2-inch-thick solid steel plate door and a 11 gauge steel body thickness to resist pry attacks and forced entry. Three large locking bolts and a bolt detent system automatically engage when the door closes to ensure it's always securely locked. Additional security measures include a carburized hardplate protecting the lock and a spring-loaded relocking device that triggers if the lock is attacked. The front-loading depository itself is designed with anti-fish baffles, preventing thieves from reaching in to pull out contents once deposited. With anchor holes for floor mounting and options for advanced electronic locks (including time-delay features on some models), the DSF Series offers reliable, everyday protection for cash-heavy environments.



Textured
Charcoal Gray

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
DSF2014	20 ¼" x 14" x 14"	9 ¾" x 9 ¾"	11 GA	0.74 cu. ft.	84 lbs.	ESL10 or ESL20
DSF2516	25" x 16" x 20"	14 ½" x 12"	11 GA	0.88 cu. ft.	155 lbs.	ESL20
DSF2714	27 ¼" x 14" x 14"	9 ¾" x 9 ¾"	11 GA	1.5 cu. ft.	96 lbs.	ESL10
DSF3214	32 ¼" x 14" x 14"	9 ¾" x 9 ¾"	11 GA	0.98 cu. ft.	138 lbs.	ESL10

- **Front-load deposit door:** Easy-access drop door on the safe's front for quick deposits without unlocking.
 - **Anti-fish hopper design:** Internal baffles and saw-tooth edges prevent fishing out envelopes once deposited.
 - **Dual-compartment security:** Separate interior locker catches deposits and stays locked, accessible only by authorized staff.
 - **B-rated all-steel construction:** 1/2-inch-thick solid steel plate door and thick steel body resist prying and drilling.
 - **Three solid steel locking bolts:** Multiple 1-inch diameter bolts secure the door tightly for enhanced break-in resistance.
- **Auto door locking system:** Bolt detent mechanism automatically locks the door bolts when the door is shut.
 - **Hardplate and relocker protection:** A hardened steel plate and spring-loaded relock device help protect the lock from drilling and punching.
 - **Time-delay lock options:** Available electronic locks offer multi-user and time-delay features.
 - **Anchoring ready:** Can be bolted to the floor to prevent removal.
 - **Ideal for retail deposits:** Keeps daily cash deposits secure, reducing theft risks.

DSR Series



Product Overview

AMSEC's DSR Series safes are rear-loading depository safes specially designed for through-the-wall deposits or any situation where deposits are made from the back side of the safe. These safes feature a reverse hopper chute that extends through a wall or partition, allowing staff or armored couriers to drop cash and valuables directly into the safe from an adjacent area. The chute's length is adjustable to fit different wall thicknesses, and it includes anti-fish baffles to prevent retrieval of deposited items from the drop opening. This unique design is ideal for businesses like convenience stores or restaurants that need to make secure deposits from a customer-facing side into a safe located in a secure back office.

The DSR Series is built to provide high-security overnight protection for cash. It carries a B-rate construction with a solid 1/2-inch-thick steel plate door and a sturdy steel body (approx. 1/8-inch-thick) that together form a strong defense against attack. Inside, the safe is divided into dual compartments: a lower till storage section that can hold several cash till trays, and a separate lockable receiving locker where dropped deposits are collected. This two-compartment system ensures deposits remain sealed off until management access. Three large locking bolts secure the door, aided by an auto-lock detent system and an auxiliary spring-loaded relocker for extra protection. Additionally, a UL-rated electronic lock with multiple user codes and a programmable time-delay feature comes standard to deter hold-up scenarios. With its heavy-duty construction and specialized rear-drop design, the DSR Series offers a secure and convenient solution for businesses requiring through-the-wall cash deposits.



Textured
Charcoal Gray

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
DSR2516	25" x 16" x 20"	14 ½" x 12"	11 GA	2.13 cu. ft.	260 lbs.	ESL20

- **Rear-loading deposit chute:** Allows secure deposits through the back of the safe.
 - **Adjustable through-wall hopper:** Deposit chute extends through walls 6-inch–14-inch thick.
 - **Dual anti-fish baffles:** Reverse hopper with saw-tooth baffles to prevent fishing out deposits.
 - **Two separate compartments:** One section for storing cash trays plus a separate locked deposit compartment.
 - **B-rated solid steel construction:** 0.5-inch-thick steel plate door and 0.125-inch-thick steel body provide strong burglary resistance.
- **Triple locking bolt system:** Three large 1-inch diameter steel bolts secure the door; auto-lock detent engages on closing.
 - **Hardplate and relocker:** Carburized hardplate and auxiliary relocking device protect against drilling and punching.
 - **High-security electronic lock:** Includes a UL Type 1 digital lock with multi-user codes and time-delay.
 - **Bolt-down installation:** Safe has anchor holes to bolt it to the floor for stability.
 - **Secure unattended deposits:** Ideal for fast-food, gas stations, or banks to drop deposits from a public side into a locked back-room safe.

BLC Series



Product Overview

AMSEC’s BLC Series safes are high-security “C”-rated plate safes built to protect daily operating funds, documents, and merchandise at an economical price. Each BLC safe features a massive 1-inch-thick solid steel plate door and a 1/2-inch-thick steel body, significantly more steel than standard B-rated safes, giving it a formidable barrier against forced entry attempts. The door is recessed and pry-resistant, fitted with a UL listed Group 2 combination lock with 1 million possible combinations, and secured by a trio of 1-inch diameter chromed steel locking bolts.

The BLC Series is engineered with comprehensive security features. A large carburized hardplate protects the lock and internal relocking devices from drilling, and a spring-loaded relocker will deadbolt the safe if the lock is punched out. The 1/2-inch-thick solid steel body is continuously welded and reinforced with a frame that gives the appearance of 1-inch-thick walls, deterring attackers by sheer strength and thickness. Inside, these safes offer versatile storage with multiple adjustable shelves for organizing cash, documents, or valuables, all in an attractive textured finish. AMSEC also offers custom interior configurations for BLC safes, complete with detailed design consultations and sketches to tailor the safe to your business needs. The BLC Series provides an affordable yet top-tier security solution for businesses requiring more protection than a standard B-rate safe.



Textured
Charcoal Gray



Chrome

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
BLC2018	21" x 19" x 16"	18 ½" x 16 ½"	½"	2.5 cu. ft.	370 lbs.	UL Group II
BLC3018	31" x 19" x 20"	28 ½" x 16 ½"	½"	5 cu. ft.	550 lbs.	UL Group II
BLC3024	31" x 25" x 24"	28 ½" x 22 ½"	½"	8.3 cu. ft.	740 lbs.	UL Group II
BLC4024	41" x 25" x 24"	38 ½" x 22 ½"	½"	11.11 cu. ft.	925 lbs.	UL Group II

- **1-inch-thick solid steel door:** Massive, pry-resistant door provides “C” rate burglary protection.
- **1/2-inch-thick solid steel body:** Heavy steel walls with reinforced frame present a formidable barrier to attacks.
- **Three 1-inch diameter chrome locking bolts:** Large steel bolts engage the door for a secure lockup.
- **Full-length hinge side dead bar:** Rigid steel dead bar prevents door removal if hinges are cut.
- **Hardplate armor:** Massive carburized hardplate protects the lock and relocker from drilling attempts.

- **Spring-loaded relock device:** Relocker triggers to keep the safe locked if the lock is punched.
- **UL-listed Group 2 lock:** High-security dial combination lock (mechanical, 1 million possible combinations).
- **Adjustable interior shelving:** Multiple shelves can be moved or removed to organize cash, documents, or valuables.
- **Custom configurations available:** Can be built in custom sizes or interiors to meet unique business needs.
- **Premium American-made quality:** Proudly built in the USA with top craftsmanship for long-term use.

BLB Series



Product Overview

AMSEC’s BLB Series safes are solidly built, economical B-rated security safes offering reliable protection for cash and valuables in a compact, customizable form factor. Each BLB safe features a 1/2-inch-thick solid steel plate door and a 1/4-inch-thick continuously welded steel body, giving it substantial burglary resistance for its size. The door is recessed to resist prying and equipped with a UL Group 2 key-changeable combination lock (with relock feature and 1 million possible combinations). When locked, a trio of 1-inch diameter chromed steel bolts secure the door, while a full-length steel dead bar on the hinge side ensures the door cannot be removed even if the hinges are cut off.

The BLB Series comes equipped with a suite of anti-theft features typically found in higher-rated safes. A large carburized hardplate protects the lock area, and if a thief attempts a brute-force attack by punching out the lock, a spring-loaded relocking device will automatically deadbolt the safe to thwart the break-in. Inside, BLB safes include adjustable shelves (usually two) to help organize your contents, and they come in an attractive gray textured finish that suits any business setting. AMSEC can customize the interior or dimensions to meet specific needs. The BLB Series delivers premium American-made security at an economical price point for small businesses, restaurants, and retail stores.



Textured
Charcoal Gray



Chrome

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
BLB2018	20 ½" x 18 ½" x 15"	18" x 16"	4 GA	2.5 cu. ft.	218 lbs.	UL Group II
BLB3018	30 ½" x 18 ½" x 19"	28" x 16"	4 GA	5 cu. ft.	312 lbs.	UL Group II
BLB3024	30 ½" x 24 ½" x 23"	28" x 22"	4 GA	8.3 cu. ft.	360 lbs.	UL Group II
BLB4024	40 ½" x 24 ½" x 23"	38" x 22"	4 GA	11.11 cu. ft.	445 lbs.	UL Group II

- **1/2-inch-thick steel plate door:** Stout door with 1/2-inch-thick solid steel resists prying and forced entry attempts.
- **1/4-inch-thick solid steel body:** Fully welded 1/4-inch-thick steel walls earn a “B” burglary rating for reliable protection.
- **Three 1-inch diameter locking bolts:** Three chrome-plated steel bolts lock the door firmly to the frame for solid security.
- **Anti-pry hinge bar:** Full-length dead bar on the hinge side prevents door removal if hinges are cut.
- **Drill-resistant hardplate:** Case-hardened steel hardplate safeguards the lock mechanism from drilling attempts.

- **Automatic relocking device:** Spring-loaded relocker activates if the lock is punched out, securing the bolts.
- **UL Group 2 combination lock:** Reliable high-security lock with 1 million combinations (electronic upgrades available).
- **Adjustable shelves:** Includes shelves that can be repositioned to organize cash, documents, and valuables.
- **Economical custom design:** Custom-built to specific size or interior needs, combining security and affordability.
- **Proudly made in the USA:** Backed by AMSEC’s 75+ years of safe manufacturing expertise.

CFX Series



Shown with optional auxiliary key lock

FIRE RATING
Rating of
120 Minutes at 1850°F

SECURITY RATING
TL-30×6 Burglary
Tool Resistant Safe

MADE IN USA

**Textured
Charcoal Gray**

Chrome

Product Overview

The CFX Series safes represent the pinnacle of commercial security, featuring UL TL-30X6 ratings that certify they withstand concentrated burglary attacks on all six sides. These high-security AMVAULTx6 safes incorporate a 3-inch-thick defense barrier in the walls, made of high-strength concrete composite enclosed by high-tensile steel, along with a massive 6-inch-thick door. This formidable construction, combined with advanced boltwork and internal reinforcements, earned the CFX Series the highest UL rating of its class, a testament to its ability to resist prying, drilling, cutting, and powerful tools on every side.

Not only are CFX safes built to thwart burglars, they also provide robust fire protection. Each safe is rated for a 2-hour fire endurance to keep contents safe from fire damage. The door is secured by a multi-directional bolt system with numerous massive locking bolts on all sides of the door, and a drill-resistant locking mechanism protected by hardened plates and relockers. Inside, the CFX offers a spacious, well-appointed interior that can be customized with drawers, shelves, or other configurations to meet your needs. All CFX models are proudly made in the USA to the highest quality standards and come equipped with UL-rated high-security locks (mechanical or electronic) for ultimate peace of mind. For jewelry stores, banks, and other high-value operations requiring maximum protection, the CFX Series delivers uncompromising security.

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Number of Shelves	Weight
CFX252016	31" x 26" x 25 ¼"	25" x 20"	3"	4.6 cu. ft.	1	1,433 lbs.
CFX352020	41" x 26" x 29 ¼"	35" x 20"	3"	8.1 cu. ft.	2	1,946 lbs.
CFX452020	51" x 26" x 29 ¼"	45" x 20"	3"	10.4 cu. ft.	3	2,343 lbs.
CFX582820	64" x 34" x 29 ¼"	58" x 28"	3"	18.8 cu. ft.	4	3,418 lbs.
CFX703620	76" x 42" x 29 ¼"	70" x 36"	3"	29.2 cu. ft.	4	4,578 lbs.
Lock Type: Combination Lock with Key-Locking Spy-Proof Dial Combination Lock with Spy-Proof Dial ESL5 ESL10						

- UL TL-30X6 high-security rating:** Certified to withstand expert burglary attacks on all 6 sides.
 - Thick composite construction:** 6-inch-thick multi-layer steel door and 3-inch-thick barrier walls with high-strength concrete fill.
 - Two-hour fire rated:** Survives intense fires with a 120-minute 1850°F fire rating, protecting interior contents.
 - Massive locking boltwork:** Multiple large-diameter locking bolts on all sides of the door provide vault-like security.
 - Drill and torch resistant:** Special composite materials and hardened steel armor defeat drills, grinders, and cutting torches.
- Advanced relocking systems:** Multiple relockers secure the safe if the lock or bolts are attacked.
 - UL-listed high-security lock:** Equipped with a UL-rated combination or digital lock that resists manipulation (time-delay capable).
 - Customizable interior:** Can be outfitted with jewelry drawers, shelves or other organizers to suit your valuables.
 - Heavy-duty design:** Extremely sturdy with robust hinges and a thick frame, deterring removal and tampering.
 - Top-tier American craftsmanship:** Proudly made in the USA for the most demanding applications.

CF Series



Shown with optional lock

FIRE RATING
Rating of
120 Minutes at 1850°F

SECURITY RATING
TL-30 Burglary
Tool Resistant Safe

MADE IN USA

**Textured
Charcoal Gray**

Satin

Product Overview

The CF Series safes (AMVAULT TL-30) are high-security composite safes that provide formidable protection for cash, jewelry, and sensitive assets. Each CF safe is constructed with a massive 6-inch-thick composite door and a 3.5-inch-thick body, filled with a special high-density composite material that blunts attacks from tools. This advanced construction gives the CF Series the strength to endure concentrated burglary attempts on the safe's front face for at least 30-minute, a level of protection often required by jewelry stores, pawn shops, and commercial operations holding substantial assets.

In addition to burglary resistance, the CF Series offers exceptional fire protection: a UL-certified 2-hour fire rating (at 1850°F) ensures the safe can survive extreme heat while keeping interior temperatures below 350°F. The CF safes feature a sophisticated boltwork mechanism with multiple massive locking bolts extending from the door into all sides of the frame when locked, thwarting prying and forced-entry attempts. A carburized hardplate and multiple relocking devices shield the safe's UL Group 2M combination lock (or optional electronic lock) from drilling or manipulation attacks. With adjustable shelving and a range of size options available, the CF Series strikes an ideal balance between top-tier security and functional storage space. Each safe is proudly made in the USA and delivers reliable, time-tested protection for high-value assets.

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Number of Shelves	Weight
CF1814	25" x 21" x 21 ½"	18" x 14"	3 ½"	1.8 cu. ft.	1	758 lbs.
CF2518	32" x 25" x 25 ½"	25" x 18"	3 ½"	4.2 cu. ft.	1	1,195 lbs.
CF3524	42" x 31" x 29 ½"	35" x 24"	3 ½"	9.7 cu. ft.	2	1,908 lbs.
CF4524	52" x 31" x 29 ½"	45" x 24"	3 ½"	12.5 cu. ft.	3	2,311 lbs.
CF5524	62" x 31" x 29 ½"	55" x 24"	3 ½"	15.3 cu. ft.	3	2,679 lbs.
CF6528	72" x 35" x 29 ½"	65" x 28"	3 ½"	21.1 cu. ft.	4	3,359 lbs.
CF7236	79" x 43" x 32 ½"	72" x 36"	3 ½"	34.5 cu. ft.	4	4,426 lbs.
Lock Type: Combination Lock with Key-Locking Spy-Proof Dial Combination Lock with Spy-Proof Dial ESL5 ESL10						

- UL TL-30 burglary certified:** Resists expert safecracking.
 - 6-inch-thick composite door:** Massive door with layers of steel and high-density composite material stops drills and saws.
 - 3.5-inch-thick reinforced body:** Thick composite walls provide a strong barrier against forced entry and heat.
 - Two-hour fire protection:** Keeps interior below 350°F for 2 hours in a 1850°F fire.
 - Robust locking bolts:** Multiple large diameter locking bolts secure the door on all sides, preventing prying attacks.
- Hardplate & relockers:** A steel hardplate and multiple relocking devices guard the lock, activating if the safe is attacked.
 - UL high-security lock:** Comes standard with a UL-listed Group 2M mechanical dial lock for reliable access control.
 - Spacious, configurable interior:** Adjustable shelves let you organize cash, jewelry, or documents in the ample space.
 - Multiple sizes available:** Offered in various dimensions to fit small business to large commercial needs.
 - Proudly USA-made:** Built in the USA with premium materials, ideal for jewelers, pawn shops, and any business needing serious security.

CE Series



FIRE RATING
Rating of
120 Minutes at 1850°F

SECURITY RATING
TL-15 Burglary
Tool Resistant Safe

MADE IN USA

Textured
Charcoal Gray

Chrome

Product Overview

AMSEC's CE Series safes (AMVAULT TL-15) provide a high level of defense for valuable assets, combining UL TL-15 rated burglary construction with robust fire protection. These safes feature a formidable 6-inch-thick composite door and a 3 1/2-inch-thick body, like the higher TL-30 models, but engineered to defeat break-in attempts under UL's rigorous testing. The CE Series leverages multiple layers of steel and proprietary composite fill to create a barrier that effectively resists prying, drilling, and cutting attacks on the safe's front.

Each safe also offers exceptional fire resistance, with a 2-hour fire rating (tested up to 1850°F) to protect contents from high-heat disasters. Security features include a heavy-duty locking mechanism with numerous large locking bolts securing all sides of the door (including an optional three-way boltwork upgrade for even more coverage). Critical areas like the lock and boltwork are guarded by hardened steel hardplates and relocking devices, which will deadlock the safe if a burglar tries to tamper with the lock. CE Series safes come standard with a UL-listed high-security lock (mechanical combination dial) that can be factory-fitted with an electronic lock for convenience. Inside, adjustable shelving or custom interior configurations allow you to organize your valuables effectively. Built in the USA with AMSEC's renowned craftsmanship, the CE Series is an excellent choice for businesses that need serious security for cash, jewelry, and important documents, with slightly more budget-friendly specs than the top-tier TL-30 safes.

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Number of Shelves	Weight
CE1814	25" x 21" x 21 ½"	18" x 14"	3 ½"	1.8 cu. ft.	1	710 lbs.
CE2518	32" x 25" x 25 ½"	25" x 18"	3 ½"	4.2 cu. ft.	1	1,105 lbs.
CE3524	42" x 31" x 29 ½"	35" x 24"	3 ½"	9.7 cu. ft.	2	1,674 lbs.
CE4524	52" x 31" x 29 ½"	45" x 24"	3 ½"	12.5 cu. ft.	3	2,200 lbs.
CE5524	62" x 31" x 29 ½"	55" x 24"	3 ½"	15.3 cu. ft.	3	2,343 lbs.
CE6528	72" x 35" x 29 ½"	65" x 28"	3 ½"	21.1 cu. ft.	4	3,153 lbs.
CE7236	79" x 43" x 32 ½"	72" x 36"	3 ½"	34.5 cu. ft.	4	4,880 lbs.

Lock Type: Combination Lock with Key-Locking Spy-Proof Dial | Combination Lock with Spy-Proof Dial | ESL5 | ESL10

- **UL TL-15 burglary rated:** Resists professional break-in attempts under test conditions.
- **Thick composite door & body:** 6-inch-thick steel composite door and 3 1/2-inch-thick reinforced walls stop prying, drilling, and cutting attacks.
- **2-hour fire rated:** Provides 120 minutes of fire protection at up to 1850°F, keeping interior contents safe from extreme heat.
- **Multi-bolt locking system:** Heavy-duty locking bolts secure the door on at least two sides (three-way boltwork optional) to thwart prying.
- **Drill-resistant lock protection:** Steel hardplates and internal relockers guard the lock; if attacked, they keep the safe locked.

- **UL-listed combination lock:** Standard UL Group 2M mechanical dial lock (optional electronic upgrade) for high-security access.
- **Internal relocking devices:** Spring triggers that secure the bolts in a forced-entry attack, preventing door opening even if the main lock is defeated.
- **Flexible interior space:** Adjustable shelves or custom interior options let you organize cash, jewelry, or files efficiently.
- **Multiple sizes offered:** Available in various dimensions to suit different capacity needs and space constraints.
- **American-made security:** Proudly built in the USA for jewelers, pawn shops, and businesses seeking top-notch security at a step below TL-30 cost.



DXE Series





SECURITY RATING
TL-15 Burglary
Tool Resistant Safe



MADE IN USA



Textured
Charcoal Gray



Product Overview

AMSEC’s DXE Series Money Chests are UL TL-15 rated high-security safes that use a solid steel design (rather than composite materials) to achieve their burglary protection. Each DXE safe is built with a 1/2-inch-thick solid steel plate door and a 1/2-inch-thick steel body, with all external seams continuously welded, creating a formidable barrier against attacks. This robust steel construction meets UL’s TL-15 standard, meaning the safe can resist sophisticated burglary tool attacks. This level of security is often required in cash-intensive businesses and financial institutions.

DXE safes feature a precision-engineered locking mechanism: a handle-activated boltwork that throws between two and six massive 1-inch diameter chromed steel locking bolts (depending on the safe’s height) to secure the door. The boltwork and lock are protected by a large, proprietary drill-shattering hardplate, and a spring-loaded auxiliary relocking device will trigger if an attacker attempts to punch out the lock. The result is that even aggressive drilling or punching attacks are thwarted. Additionally, a solid steel full-length dead bar locks into the door frame on the hinge side, preventing the door from being removed if the hinges are cut during a forced entry. The DXE Series comes standard with a UL Listed Group 2M mechanical combination lock, offering 1 million possible combinations and the reliability needed for commercial use. With oil-impregnated bearing hinges for smooth door operation and optional interior configurations (like adjustable shelves or door-mounted coin racks), these safes can be tailored to your needs. Available in a broad range of sizes from compact chests under 2 cubic feet to large vaults over 30 cubic feet, the DXE Series provides flexible, top-tier security for businesses requiring UL-rated protection in an all-steel safe.

- **UL TL-15 rated steel safe:** Heavy all-steel safe, UL TL-15 tested against tool attacks.
 - **Solid plate steel build:** 1/2-inch-thick solid steel door and 1/2-inch-thick solid steel body deliver TL-15 strength without composite material.
 - **Continuously welded seams:** All exterior seams are beveled and fully welded for maximum rigidity and security.
 - **Massive locking bolts:** Depending on size, 2–6 large 1-inch diameter chromed steel bolts lock the door via a robust handle-driven mechanism.
 - **Hinge-side dead bar:** Full-length solid steel dead bar secures the door on the hinge side, preventing removal even if hinges are cut.
- **Hardplate armor protection:** Proprietary drill-resistant hardplate defends the lock and critical areas from drilling or tampering.
 - **Auxiliary relocker:** Spring-loaded relock device triggers if the lock is punched out, freezing the boltwork in the locked position.
 - **UL Group 2 combo lock:** Standard UL-listed key-changeable combination lock (1,000,000 combos) for high security.
 - **Wide range of sizes:** Available in heights from ~10-inch up to 88-inch, with ~2 to 30+ cubic ft capacity range.
 - **Built for cash security:** Ideal “money chest” safe for banks, retail, or any business seeking top-tier steel protection without composite materials.

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight
DXE1414	15 ½" x 15 ½" x 16 ¼"	13 ½" x 13 ¼"	½"	1.46 cu. ft.	240 lbs.
DXE1818	19 ½" x 19 ½" x 16 ¼"	17 ½" x 16 ¾"	½"	2.37 cu. ft.	325 lbs.
DXE2020	21 ½" x 21 ½" x 24 ¼"	19 ½" x 18 ¾"	½"	4.86 cu. ft.	464 lbs.
DXE2420	25 ½" x 21 ½" x 24 ¼"	23 ½" x 18 ¾"	½"	5.81 cu. ft.	513 lbs.
DXE2424XD	25 ½" x 25 ½" x 28 ¼"	23 ½" x 18 ¾"	½"	8.33 cu. ft.	635 lbs.
DXE3018XD	31 ½" x 19 ½" x 24 ¼"	29 ½" x 16 ¾"	½"	6.53 cu. ft.	574 lbs.
DXE3024	31 ½" x 25 ½" x 24 ¼"	29 ½" x 16 ¾"	½"	8.65 cu. ft.	673 lbs.
DXE3030	31 ½" x 31 ½" x 24 ¼"	29 ½" x 28 ¾"	½"	10.76 cu. ft.	770 lbs.
DXE4024	41 ½" x 25 ½" x 24 ¼"	39 ½" x 22 ¾"	½"	11.48 cu. ft.	821 lbs.
DXE4524	46 ½" x 25 ½" x 24 ¼"	44 ½" x 22 ¾"	½"	12.90 cu. ft.	897 lbs.
DXE5030	51 ½" x 31 ½" x 24 ¼"	49 ½" x 28 ¾"	½"	17.82 cu. ft.	1,103 lbs.
DXE5224	53 ½" x 25 ½" x 24 ¼"	51 ½" x 22 ¾"	½"	14.88 cu. ft.	1,100 lbs.
DXE6030	61 ½" x 31 ½" x 24 ¼"	59 ½" x 28 ¾"	½"	21.35 cu. ft.	1,274 lbs.
DXE7234	73 ½" x 35 ½" x 30 ¼"	71 ½" x 32 ¾"	½"	37.63 cu. ft.	1,775 lbs.
Lock Type: Combination Lock with Key-Locking Spy-Proof Dial Combination Lock with Spy-Proof Dial ESL5 ESL10					

ACF Series



Shown with optional S&G lock kit

Product Overview

AMSEC’s ACF Series safes are among the most secure and versatile safes available, offering UL TL-30 high-security protection with a fully customizable design. These safes are constructed with the same advanced materials found in AMSEC’s AMVAULT line, including thick composite steel barriers in the walls and door that can defeat concentrated attacks from powerful tools. Businesses can work with AMSEC to tailor dimensions, interior configurations (lockers, shelves, coin racks, etc.), and locking options to create a safe that precisely fits their operational needs.

Despite the heavy-duty security, the ACF Series doesn’t compromise on functionality. For example, an ACF depository safe might feature a top-loading rotary hopper or a front deposit drawer so employees can drop cash into a secured inner vault, providing high-security overnight storage for deposits. Standard ACF safes come equipped with UL-rated high-security locks (with choices of combination dials or electronic locks with audit features), multiple large locking bolts on all sides of the door, relocking devices, and thick alloy hardplates to shield against drilling. Fire protection can be incorporated as well, often achieving a 2-hour fire rating like other composite safes. Because each ACF safe is essentially custom-made, clients receive detailed design consultations and drawings before fabrication to ensure the safe meets all requirements. If your security scenario demands the absolute best, be it a specialized cash vault, a unique size constraint, or integrated deposit capability, the ACF Series provides high-security peace of mind tailored to you.

- **UL TL-30 high-security safe:** Built to UL TL-30 specs, withstands intensive burglary tool attacks.
 - **Custom-built to order:** Fully customizable in size, interior configuration, and special features to meet your needs.
 - **Composite armor construction:** Thick multi-layer steel and concrete composite walls and door resist drilling, cutting, and prying attacks.
 - **Locking bolts:** Heavy-duty multi-bolt system locks the door, with spring-loaded relockers that engage if the safe is attacked.
 - **Standard fire protection:** built with fire-resistant materials to achieve up to a 2-hour fire rating.
- **Advanced locking choices:** Available with UL-listed combination locks or electronic locks (audit trail, time delay, etc.) for controlled access and accountability.
 - **Interior tailored to you:** Configure the inside with adjustable shelves, lockable compartments, cash till slots, or other features to suit your workflow.
 - **Built for overnight cash security:** Ideal for banks, armored transport, or large retailers needing overnight deposit security.
 - **Premium craftsmanship:** Handcrafted in the USA by AMSEC, delivering elite protection and customized solutions for the most demanding requirements.



Shown with optional auxiliary key lock



FIRE RATING
Rating of
120 Minutes at 1800°F



SECURITY RATING
TL-30 Burglary
Tool Resistant Safe



MADE IN USA



**Textured
Charcoal Gray**



Chrome

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight
ACF2020	26 ¾" x 26 ½" x 29"	19" x 18 ¾"	3 ¼"	4.63 cu. ft.	1,069 lbs.
ACF2020XD	26 ¾" x 26 ½" x 33"	19" x 18 ¾"	3 ¼"	5.55 cu. ft.	1,170 lbs.
ACF3020	36 ¾" x 26 ½" x 29"	29" x 18 ¾"	3 ¼"	6.94 cu. ft.	1,369 lbs.
ACF3020XD	36 ¾" x 26 ½" x 33"	29" x 18 ¾"	3 ¼"	8.33 cu. ft.	1,492 lbs.
ACF4024	46 ¾" x 30 ½" x 29"	39" x 22 ¾"	3 ¼"	11.11 cu. ft.	1,849 lbs.
ACF4024XD	46 ¾" x 30 ½" x 33"	39" x 22 ¾"	3 ¼"	13.33 cu. ft.	2,003 lbs.
ACF5024	56 ¾" x 30 ½" x 29"	49" x 22 ¾"	3 ¼"	13.88 cu. ft.	2,176 lbs.
ACF5024XD	56 ¾" x 30 ½" x 33"	49" x 22 ¾"	3 ¼"	16.66 cu. ft.	2,351 lbs.
ACF6030	66 ¾" x 36 ½" x 29"	59" x 28 ¾"	3 ¼"	20.83 cu. ft.	2,847 lbs.
ACF6030XD	66 ¾" x 36 ½" x 35"	59" x 28 ¾"	3 ¼"	27.08 cu. ft.	3,162 lbs.
ACF4824DS	47 ¾" x 24 ½" x 26"	TOP: 25" x 16 ¾" BTM: 13" x 16 ¾"	3 ¼"	3.79 cu. ft. 2.48 cu. ft.	1,746 lbs.

Lock Type: Combination Lock with Front-Read Dial | Combination Lock with Key-Locking Front-Read Dial
Combination Lock with Key-Locking Spy-Proof Dial | Combination Lock with Spy-Proof Dial | ESL5 | ESL10
ACF4824DS: Group 2M Combination Lock Both Doors & AUX Key Lock Bottom Compartment

TB Series



Product Overview

AMSEC’s TB Series are compact under-counter drop boxes designed for point-of-sale cash security. These small safes (e.g. model TB0610) are constructed of solid steel and feature a full-width slot over the door for inserting cash, checks, or envelopes. An integrated saw-toothed “anti-fish” baffle guards the slot to prevent anyone from reaching in or using tools to pull out the contents. The door itself is secured by a heavy-duty piano hinge and opens with a key; the series offers several lock options, from standard cam locks to 7-pin tubular locks or high-security Medeco key locks, depending on your needs.

The TB Series boxes are designed to be versatile and tamper-resistant. Each unit has pre-drilled bolt holes on every side, allowing you to mount it securely beneath counters or to bolt multiple TB boxes together (side-by-side or back-to-back) for multiple registers. This flexibility ensures the drop box stays in place and cannot be easily removed or stolen. For added convenience, the doors are interchangeable, you can swap out the entire door and lock assembly if you need to upgrade or change the lock without replacing the box. Though compact (about 8 lbs in weight), TB Series drop safes offer an extra layer of protection for daily cash handling by getting bills out of the register and into a locked container quickly. They are an economical solution to reduce grab-and-go theft and increase accountability at the point of sale, making them ideal for retail stores, restaurants, and any business with cash tills.



Textured Black

Model	Outside Dimensions H x W x D	Door Clearance H x W	Body Thickness	Interior Capacity	Weight	Lock Type
TB0610-1	6" x 6" x 10"	5 7⁄8" x 5"	16 GA	0.16 cu. ft.	8 lbs.	Single-Key Camlock
TB0610-1T	6" x 6" x 10"	5 7⁄8" x 5"	16 GA	0.16 cu. ft.	8 lbs.	Chicago 7-Pin Radial Key Camlock
TB0610-2	6" x 6" x 10"	5 7⁄8" x 5"	16 GA	0.16 cu. ft.	8 lbs.	Medeco Single-Key Camlock

- **Compact deposit box:** Small under-counter safe to secure daily cash drops at registers.
 - **Solid steel construction:** Sturdy, all-steel build with welded seams provides reliable protection in a compact form.
 - **Anti-fish baffle:** Saw-tooth baffle in the slot prevents thieves from “fishing” out the contents once deposited.
 - **Heavy-duty door hinge:** Continuous piano hinge supports the door and thwarts prying attempts on the hinge side.
 - **Interchangeable door/lock:** Door and lock assembly can be swapped out, allowing easy lock upgrades or changes (excludes K1 model).
- **Multiple lock options:** Offered with cam, tubular, or high-security key locks to fit your needs.
 - **Wide deposit slot:** Full-width slot above the door easily accepts cash, checks, and envelopes for quick deposits.
 - **Bolt-together design:** Bolt holes on all sides enable secure mounting under counters or linking multiple units together.
 - **Versatile mounting:** Can be anchored to countertops, walls, or floors so it stays fixed in place and cannot be removed.
 - **Quick cash security:** Immediately secures excess cash from registers, discouraging grab-and-run theft and improving cashier accountability.

AMSEC Electronic Locks



	ESL5	ESL5LP	Backlit ESL10	Backlit ESL20	ESLAudit II	SafeWizard II®
Keypad Housing	Round Backlit	Backlit	Round Backlit	Round Backlit	Vertical Rectangle	Horizontal Rectangle
UL Listed	UL Type 1	UL Type 1	UL Type 1	UL Type 1	UL Type 1	–
Number of Users	1	1	1	1 Master, 8 Users, 1 Armored Car	40 Multiple User Options	500 Multiple User Options
Time Delay Override	no	No	No	Yes	Yes	Yes
Safe Doors	1	1	1	1	4	12
Power Source	(1) 9V	(1) 9V	(2) 9V	(2) 9V	(2) 9V A/C Opt.	AC w/Battery Back-up
Combination (# of Digits)	6	6	6	6	Key + 6 Digits, 8 if keypad only	Key + 6 Digits, 8 if keypad only
Wrong Try Lock Out (time)	Yes (15 min.)	Yes (15 min.)	Yes (15 min.)	Yes (15 min.)	Yes - 4 attempts (15 min.)	User Settable
Dual Mode	–	–	–	Yes	Yes	Yes
Time Delay	–	–	–	1-99 min.	1-99 min.	1-99 min.
Time Delay Open Input Window (time by user)	–	–	–	1-9 min.	1-99 min.	1-99 min.
Time Lock (Periods) *(Variable)	–	–	–	–	(4)(*) Software Set	(6)(*)
Duress	–	–	–	–	Optional	Standard
Audit Trail (# of events)	–	–	–	–	5000 Time & Date Software Viewed	120,2000 w/ 500 Back-up Time & Date
PC Software Audit Trails	–	–	–	–	Optional	Cloud (Optional)
Alarm Interface	–	–	–	–	Optional	Yes
Auto Lock	Yes	Yes	Yes	Yes	Yes	Yes
Bolt Options	Swing	Swing	Standard/Slam	Standard/Slam	Swing/Toggle	Swing/Toggle
Color Options	Chrome	Matte Black	Chrome, Brass, Black Nickel, Matte Black	Matte Black	Brushed Satin Chrome	Silver/Blue

Partner Electronic Locks

	SARGENT & GREENLEAF		KABA		
	6123	6126	AuditCon 52	AuditCon 252	AuditCon 552
Keypad Housing	Round	Round	Round, Vertical	Round, Vertical	Round, Vertical
UL Listed	UL Type 1	UL Type 1	UL Type 1	UL Type 1	UL Type 1
Number of Users	5	1 Programmer, 3 Manager, 6 Super Users, 20 Users	2	20	99
Time Delay Override	Yes	Yes	–	Yes	Yes
Safe Doors	1	1	1	1	1
Power Source	(2) 9V	(2) 9V	Self-Generating / Battery	Self Generating	Self Generating
Combination (# of Digits)	6	6	6	8	8
Wrong Try Lock Out (time)	4 (15 min.)	5 (15 min.)	Yes (3 min.)	Yes (3 min.)	Yes (3 min.)
Dual Mode	Yes	Yes	Yes	Yes	Yes
Time Delay	1-99 min.	1-99 min.	Yes {Order Model T-52}	Yes	Yes
Time Delay Open Input Window (time by user)	2-9 min.	1-10 min.	–	–	–
Time Lock (periods) *(variable)	–	–	–	–	–
Duress	Optional	Optional	Optional	Optional	Optional
Audit Trail (# of events)	–	400 Time & Date	–	–	400 Time & Date
PC Software Audit Trails	–	Optional Audit Only	–	(Optional) 100	(Optional) 400
Alarm Interface	–	Yes	–	Yes (optional)	Yes (Optional)
Auto Lock	Yes	Yes	Yes	Yes	Yes
Bolt Options	Standard Motor	Standard Motor	Slide/Standard	Slide/Standard	Slide/Standard

Partner Mechanical Locks

UL LISTED GROUP 2 MECHANICAL COMBINATION SAFE LOCK KIT

Mechanical combination safe locks have been around for over 100 years and are very secure and reliable. With the proper care and service, the mechanical combination safe lock will last a long time.

- Three bass and aluminum combination wheels provide 1,000,000 theoretical combinations
- Dual brass locking cams prevent wheel slippage
- Solid brass locking bolt and zinc drop lever
- Four-way brass drive cam allows mounting RH, LH, VU or VD
- Internal spring -loaded brass relock-trigger guards against punch attacks
- Standard mounting footprint matches most mechanical and electronic safe locks
- Both dial and ring are die cast with black finish and white letters
- A solid, machined brass spindle - 5 1/2"
- Comes standard with an attractive self-stick solid dial insert or a key-locking dial insert

SAFE LOCK KIT INCLUDES

- Mechanical safe lock
- Large dial & ring
- Combination change key
- Mounting hardware



SPY PROOF KEY LOCKING DIAL

Restricts unauthorized viewing while dialing the combination, as well as providing dual custody control.



FRONT READ DIAL

Safe is equipped with Time Locks offer the capability of locking the safe for a pre-selected period of time. Time periods range from 1 hour to 144 hours.



SPY PROOF DIAL

Restricts unauthorized viewing while dialing the combination.



UL LISTED HIGH SECURITY KEY LOCK

European style 9-lever changeable key lock offers exceptional security features for use on inner locker or outer safe doors.



KEY LOCKING FRONT READ DIAL

Key is used to lock dial in a fixed position and affords dual custody control. Manager has the combination, collector has the key. Both must be present to unlock the safe.

